

**Section 1 - Identification of the substance/mixture and of the company/undertaking**

**1.1 Product Identifier**

**Product name** Lightspeed  
**Product code** Lightspeed kit: LSP15K, LSKIT  
**Restriction of use** Refer to Section 15

**1.2 Relevant identified uses of the substrate or mixture and uses advised against**

**Identified uses** Protective coating for underwater lights.

**1.3 Details of the supplier of the Safety Data Sheet**

**Supplier** Propspeed USA Inc.  
 20403 Encino Ledge #591520  
 PO BOX 591520  
 San Antonio, TX 78259  
 USA  
 www.propspeed.com

**Telephone** +1 754 232 8227

**1.4 Emergency telephone number**

**Emergency Response Telephone** USA & Canada Call CHEMTREC // Toll Free: 1-800-424-9300/  
 +1 703-527-3887  
 New Zealand 0800 243 622  
 Australian 1800 127 406  
 Global Access +64 4 917 9888  
**E-mail (competent person)** info@propspeed.com

**NZ National Poisons Centre Telephone** 0800 POISON (0800 764 766)

**Section 2 - Hazards identification**

**2.1 Classification of the substance or mixture**

**Hazardous Status:** This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

**EPA Approval Code:** Surface Coatings and Colourants (Flammable) - HSR002662

**GHS Pictograms:**



GHS Signal Word: **WARNING**

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
3.1C	H226	Flammable liquid and vapour	Flam. Liq. 3
6.1E (dermal)	H313	May be harmful in contact with skin.	Acute Tax. 5
6.3A	H315	Causes skin irritation.	Skin Irrit. 2
6.4A	H319	Causes serious eye irritation.	Eye Irrit. 2A
6.8B	H361	Suspected of damaging fertility or the unborn child	Repr. 2
6.9B	H373	May cause damage to organs through prolonged or repeated exposure.	STOT RE 2
6.9N	H336	May cause drowsiness or dizziness.	STOT SE 3
9.1D	H402	Harmful to aquatic life (chronic).	Aqua.4
9.3C	H433	Harmful to terrestrial vertebrates.	-

Prevention Code	Prevention Statement
P102	Keep out of reach of children
P103	Read label before use
P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat, sparks, open flames, or hot surfaces. No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical, ventilation and lighting
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P260	Do not breathe fumes, vapours and spray
P264	Wash hands thoroughly after handling
P271	Use only outdoors or in a well-ventilated area
P273	Avoid release to the environment
P280	Wear protective clothing as detailed in Section 8
P281	Use personal protective equipment as required

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P314	Get medical advice/attention if you feel unwell
P362	Take off contaminated clothing and wash before re-use
P302 + P352	IF ON SKIN: Wash with plenty of soap and water
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308 + P313	If exposed or concerned: Get medical advice/attention
P332 + P313	If skin irritation occurs: Get medical advice/attention
P337 + P313	If eye irritation persists: Get medical advice/attention
P370 + P378	In case of fire: Use AFFF alcohol compatible foam or water spray for extinction

Storage Code	Storage Statement
--------------	-------------------

P405	Store locked up
P403 + P233	Store in a well-ventilated place. Keep container tightly closed
P403 + P235	Store in a well-ventilated place. Keep cool

Disposal Code	Disposal Statement
P501	Dispose of according to local regulations

## Section 3 - Composition/information on ingredients

### 3.1 Substances

#### Hazard components

Ingredient name	Cas Number	Content Weight %
1-Propanamine,3-(triethoxysilyl)-	919-30-2	0.1 – 1
Xylene	1330-20-7	5 – 10
Ethylbenzene	100-41-4	5 – 10
White mineral oil (Pefroleum)	8042-47-5	1 – 5
2-Butanone, oxime	96-29-7	0.1 – 1

## Section 4 – First Aid Measures

### 4.1 Description of first aid measures

#### Following burns:

Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

#### Following inhalation:

Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if needed.

#### Following skin contact:

Remove contaminated clothing immediately and wash skin with soap and water. Important to remove the substance from the skin immediately. Continue to rinse for at least 15 minutes and seek medical attention.

#### Following eye contact:

Immediately flush with plenty of water. Remove any contact lenses and open eyes wide apart. Call an ambulance and continue flushing during transportation to hospital. Bring these instructions.

#### Following ingestion:

Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician immediately.

#### Symptoms

Ingestion:	Not applicable
Inhalation:	Not applicable
Skin:	May be harmful in contact with skin. Causes skin irritation.
Eye:	Causes serious eye irritation
Chronic:	Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

## Section 5 – Fire Fighting Measures

### 5.1 Extinguishing media

### Suitable extinguishing media:

On large fires use AFFF alcohol compatible foam or water spray (fog). On small fires use AFFF alcohol compatible foam, CO<sub>2</sub> or water spray (fog). Water can be used to cool fire exposed containers. Most fire extinguishing media will cause hydrogen release. Thus, in poorly ventilated or confined spaces, the accumulation of hydrogen may result in flash fire or explosion if ignited. Applying foam may release flammable hydrogen gas that can be trapped under the foam. Unsuitable: Dry powder. Do not allow extinguishing medium to contact container contents

### 5.5 Hazchem Code

3Y

<b>Hazard Type</b>	Flammable liquid
<b>Hazards from decomposition products</b>	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Hydrogen, nitrogen products.
<b>Precautions for firefighters and special protective clothing</b>	A self-contained respirator and protective clothing should be worn. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool. Vapours may form explosive mixtures with air.

### Section 6 - Accidental Release Measures

Wear protective PVC gloves, chemical goggles, and PVC boots. Contain spill with earth and sand. Where practical, transfer spilt material to clean polyethylene containers for disposal. Transfer contaminated earth or sand into polyethylene containers for disposal. Wash down area with excess water. Do not allow to drain or watercourse.

Dispose of solid residues in chemical waste disposal area in accordance with relevant Local Council requirements. Use licensed trade waste contractor to dispose of all chemical residues.

### Section 7 - Handling and Storage

#### 7.1 Precautions for safe handling

- Keep out of reach of children.
- Read label before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames and hot surfaces. No smoking.
- Keep container tightly closed.
- Use explosion proof electrical equipment, ventilation, lighting.
- Ground/bond container and receiving equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid breathing fumes, vapours, or sprays.
- Wash hands thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- Avoid release to the environment.
- Wear protective clothing and protective equipment.

#### 7.2 Conditions for safe storage, including any incompatibilities

- Store away from incompatible materials listed in Section 10
- Store in a flameproof, well-ventilated area.
- Electrostatic charges may be generated during transfer of product from its container.

- Ensure that all equipment is electrically earthed.
- Keep container closed and store away from water or moisture.
- This product may evolve hydrogen on storage.
- Vapours may form explosive mixtures with air.
- Do not store with oxidizing agents.
- Store locked up.

## Section 8 - Exposure Controls / Personal Protection

### 8.1 Control parameters

**WORKPLACE EXPOSURE STANDARDS** (provided for guidance only)

Substance	CAS	WES-TWA		WES-STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Xylene	1330-20-7	50	217	-	-

NZ Workplace Exposure Standard and Biological Exposure Indices - Nov 2017. The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

### 8.2 Exposure controls

#### Engineering Controls:

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapours. An eye wash bottle must be available at the work site. Mix and prepare in a place with efficient exhaust ventilation.

#### Personal Protection Equipment



Respiratory	Suitable respiratory protection should be worn in confined spaces or in case of inadequate ventilation. A suitable respirator must be worn if an aerosol or mist is generated.
Hands	Wear protective gloves. Nitrile gloves are recommended.
Eyes	Tight fitting safety goggles or face shield should be used. Avoid wearing contact lenses.
Skin	Wear impervious overalls if significant skin contact is likely to occur.
Hygiene	Exercise proper industrial hygiene practices. Wash hands after handling, especially before eating, smoking or drinking. Contaminated clothing should be removed immediately.

## Section 9 - Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

Appearance	Liquid
Colour	Translucent
Odour	Solvent / Petrol

Product Name: Lightspeed  
Date of SDS: 07 April 2021

Odour Threshold	Not available
pH	Not applicable (solvent based product)
Boiling Point	135 – 145°C
Melting Point	Not available
Freezing Point	Not available
Flash Point	23°C
Flammability	Not available
Upper and Lower Explosive Limits	1.1 – 7 vol %
Vapour Pressure	1,335 Pa
Relative Vapour Density	3.7 (air=1)
Specific Gravity	0.94 - 1.1
Water Solubility	Insoluble in water, soluble in organic solvents
Partition Coefficient:	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity @ 25°C	500-800cP
Particle Characteristics	Not available

## Section 10 – Stability and Reactivity

### 10.1 Chemical stability

Stable under normal conditions

### 10.2 Possibility of hazardous reactions

No data available.

### 10.3 Conditions to avoid

Avoid heat, flames and other sources of ignition.

### 10.4 Incompatible materials

Hydrogen is liberated on contact with water, alcohols, acidic or basic materials, many metals or metallic compounds and can form explosive mixtures in the air. Can react with strong oxidizing agents.

### 10.5 Hazardous decomposition products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Hydrogen, nitrogen products.

## Section 11 - Toxicological Information

### Acute Effects:

Swallowed	Small amounts transferred to the mouth by fingers during use should not injure. Swallowing large amounts may cause digestive discomfort. Forms methanol and may cause serious injury to man at doses > 200mg/kg
Dermal	May be harmful if in contact with skin.
Inhalation	Not applicable.
Eye	Causes serious eye irritation.
Skin	Causes skin irritation. Repeated or prolonged contact may cause defatting of the skin leading to dermatitis.

### Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive Toxicity	Suspected of damaging fertility or the unborn child.
Germ Cell Mutagenicity	Not applicable.
Aspiration	Not applicable.
STOT/SE	May cause drowsiness or dizziness.
STOT/RE	May cause damage to organs through prolonged or repeated exposure.

### Ingredient Data Acute

#### Oral Toxicity

Xylene LD50 (mouse) =1700 mg/kg

#### Inhalation

Xylene LD50 (rat) =29.08mg/kg

#### Special circumstances:

Formaldehyde may be produced by thermal decomposition in a fire; Formaldehyde is a suspected carcinogen, toxic by inhalation, and irritating to eyes and the respiratory system. Exposure limits should be strictly respected.

## Section 12 - Ecotoxicological Information

#### HSNO Classifications:

9.1D = Harmful to aquatic life.  
9.3C = Harmful to terrestrial vertebrates.

#### Environmental Precautions

Persistence and degradability Silicone content, biologically not degradable.

Bioaccumulation No bioaccumulation predicted

Mobility in Soil Siloxanes are removed from water by sedimentation or binding to sewage sludge. In soil, siloxanes are degraded. This product hydrolyses in water or moist air, releasing methanol and organosilicons. This product contains volatile substances which may spread in the atmosphere.

Other adverse effects No data available

## Section 13 - Disposal Considerations

### 13.1 Disposal Method

Spent media that has removed toxic chemicals should be examined for specific hazards. Dispose of according to Local Regulations.

Ensure any container holding waste product or contaminated spill media is labelled "Hazardous Waste – Flammable", and that the label also has the Flammable Pictogram, waste type identifier, and the business name, address, and phone number.

**Precautions or methods to avoid:** Avoid release to the environment.

## Section 14 – Transport Information

This product is classified as a Dangerous Good for transport in NZ; NZS 5433:2012



	Road and Rail	Marine Transport (IMDG)	Air Transport (IATA)
UN No	1263	1263	1263
Proper Shipping Name	PAINT	PAINT	PAINT
Class	3	3	3
Packing Group	III	III	III
Hazchem	3Y	3Y	3Y

**Limited Quantities Statement:**

If the product's individual container is below 5L/kg, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

**Section 15 – Regulatory Information**

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Surface Coatings and Colourants (Flammable) – HSR002662

HSNO Classes: 3.1C, 6.1E (dermal), 6.3A, 6.4A, 6.8B, 6.9B, 6.9N 9.1D, 9.3C

HSNO Controls

Trigger quantities for this substance:

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	500L(>5L), 1500L (<5L), 250L open (3.1C)
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1000L(3.1C)
Emergency Response Plan	10,000L (3.1C, 9.1D)
Secondary Containment	10,000L (3.1C, 9.1D)
Fire Extinguishers	At least 2 x 4.5kg powder extinguishers required when 500L is present in a workplace.
Restriction of Use	Only use for the intended purpose.

**Section 16 – Other Information****Glossary**

EC50	Median effective concentration
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms
HSW	Health and Safety at Work.
LC50	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD50	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
STOT/SE	Specific target organ toxicity – single exposure

Product Name: Lightspeed

Date of SDS: 07 April 2021



STOT/RE	Specific target organ toxicity – repeated exposure
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2012
5. HSW (Hazardous Substances) Regulations 2017

**Issue Date:** 07 April 2021

**Review Date:** 06 April 2023

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ("SDS"). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS. The information herein is given in good faith, but no warranty, express or implied is made. Please contact the New Zealand distributor, if further information is required.